



STANDARD INSTALLATION DETAIL

CURB OPENING INSTALLATION DETAIL

INSTALLATION AND USE GUIDELINES

- FOR INSTALLATION OF THE INLET SACK IN A CATCH BASIN
 - PULL THE GRATE FROM THE CATCH BASIN AND PLACE THE INLET BAG IN THE OPENING.
 - KEEP 6-INCHES OF THE BAG ABOVE THE FRAME OF THE BASIN
 - REPLACE THE GRATE ON THE BASIN TO KEEP THE BAG IN PLACE.
- IF SEDIMENT IS COVERING THE ORANGE RESTRAINT CORD THEN IT IS TIME TO EMPTY THE INLET BAG
- TO REMOVE THE INLET BAG
 - INSERT TWO PIECES OF 1" DIAMETER REBAR THROUGH THE LIFTING LOOPS ON EACH SIDE OF THE BAG
 - LIFT THE BAG AND GRATE FROM THE CATCH BASIN
- TO EMPTY THE INLET BAG
 - PLACE THE BAG WHERE IT IS TO BE EMPTIED
 - INSERT A REBAR THROUGH THE BOTTOM STRAPS AND LIFT
 - THE BAG WILL LIFT FROM THE BOTTOM AND POUR OUT THE SEDIMENT
 - CLEAN OUT THE BAG AND RINSE
 - RETURN THE BAG TO ITS ORIGINAL SHAPE AND PLACE IT BACK INTO THE CATCH BASIN
- THE INLET BAG IS A REUSABLE PRODUCT. WHEN THE PROJECT IS COMPLETED, REMOVE THE INLET BAG FROM THE CATCH BASINS AND CLEAN. STORE THE INLET BAGS OUT OF DIRECT SUNLIGHT UNTIL THE NEXT PROJECT.

WORK SHALL ENCOMPASS THE PROVIDING, INSTALLING, MAINTAINING, AND REMOVING THE INLET PRO SEDIMENT BAG PRODUCT AS INSTRUCTED BY THE PROJECT ENGINEER OR AS SHOWN ON THE PROVIDED SITE DRAWINGS. INLET PRO SEDIMENT BAG PRODUCTS ARE MANUFACTURED BY:

HANES GEO COMPONENTS
815 BUXTON STREET
WINSTON SALEM, NC 27101
PH: 888-239-4539 - FAX: 336-747-1652
www.hanesgeo.com
info@hanesgeo.com



2-17-2014

HGC IPSB

SHEET 1 OF 1

HANES GEO COMPONENTS INLET PRO SEDIMENT BAG